



2010 SPECIAL REFURBISHED MODEL 5001

EMS
EMISSIONS SYSTEMS, INC.

HOW CAN YOU GO WRONG WITH THIS ORIGINAL EMS MODEL?

- ✓ 1 YEAR WARRANTY ALL PARTS AND LABOR,
- ✓ 25 FT. SAMPLE HOSE, HANDLE S.S. TIP,
- ✓ EMS WINDOWS DIAGNOSTIC SOFTWARE

2 900 \$

Quantité limitée et Période Limitée

SPECIFICATIONS TECHNIQUES

Power:	10-16 VDC (110/220 VAC 50/60Hz optional)
Ranges:	HC: 0 - 2000 ppm CO: 0 - 10% CO2: 0 -20% O2: 0- 25% NOx: 0 - 5000 ppm (Nitric Oxide) *
Warm Up	Less than 10 minutes at 20C - self controlled
Display Resolution	HC: 1ppm vol. CO: 0.01% vol. CO2: 0.1% vol. O2: 0.01% vol. NOx: 1 ppm*
Digital Display	Four 0.5" LCD
Accuracy (Bar 97 EPA ASM)	HC: 4ppm HC CO: 0.06% CO CO2: 0.3% CO2 O2: 0.01% O2 NOx: 25 ppm*
Drift	Zero & span drift are less than +/- 0.6% of full scale for the first hour and less than +/- 0.4% of full scale per hour thereafter.
System Response Time	9 seconds to 90% of final reading
Ambient Conditions:	35F (2C) to 120F (45C), rel. humidity 0-98%
Sample House:	25 feet (7.5m) with quick connect coupling
Sample Probe:	Stainless Steel (replaceable flex tip)
Mass:	Approx: 12 LBS (6Kg)